

ACCESSORIES



Single wire 1500mm/3000mm long adjustable suspension kit.

46AA13
46AA1330



Ceiling mounting kit.

46AA14



3-5-7-10 powered supply box. Cable length 2000mm.

00AA16
00AA165P
00AA167P
00AA1610P



End caps kit (length: 7mm - already included in the product total length).

46AA09
46AA09AS - asymmetric



Electrified linear joint.

46AA11



2 ways joint (dim: 316x316mm).

46AA05




3 ways joint (dim: 316x570mm).

46AA06



4 ways joint (dim: 570x570mm).

46AA07



2 ways luminous joint 90° (dim: 316x316mm).

46DR12K4A90:

12W 4000K

46DR12K3A90:

12W 3000K

46DR24K4A90HP:

24W 4000K high power

46DR24K3A90HP:

24W 3000K high power



CLD optic (collimated diffuser, UGR<16) 5-10m coil to be cut on site, to provide continuous and gap-free light diffusion interruptions.

46CLD5000

46CLD10000



Satin methacrylate diffuser, 5-10m coil to be cut on site, to provide continuous and gap-free light diffusion.

46PG5000

46PG10000



Optional transparent diffuser, 5-10m coil to be cut on site, to provide continuous and gap-free light diffusion.

46TR5000

46TR10000



Blind module.

46MC1M: 1000mm

46MC2M: 2000mm