BEN

ID 10





BEN PG



CE | C | RETILAP | 5 YEARS WARRANTY | ETL Intertek

IP 40 | -20° +35° | CRI>90 | RG0/RG1 | MacAdam 3 | L90/B10 50.000h

Body


Epoxy
powder coated
aluminium

BEN / SMALL PG

SUSPENDED CEILING

PG diffuser with frosted Acryl-Satiné and impact resistant diffuser UGR<22.





CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
10PG6K4	798	10PG6K3	742	6W	257
10PG12K4	1598	10PG12K3	1486	12W	257
10PG18K4	2394	10PG18K3	2226	18W	257

BEN / SMALL PG DOUBLE EMISSION

PG diffuser with frosted Acryl-Satiné and impact resistant diffuser UGR<22. Direct/indirect emission.





CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
10DI15PGK4	2014	10DI15PGK3	1889	15W: 6W+9W	257
10DI21PGK4	2814	10DI21PGK3	2633	21W: 12W+9W	257
10DI27PGK4	3610	10DI27PGK3	3373	27W: 18W+9W	257

CE | C | RETILAP | 5 YEARS WARRANTY | ETL Intertek

IP 40 | -20° +35° | CRI>90 | RG0/RG1 | MacAdam 3 | L90/B10 50.000h

On req.: DALI CODE — D | BT | 1 h EM | 1h DEM | 3 h EM | DEM | EM3H | RHL ESSE-CI | CODE K27 2700K

Body

Epoxy
powder coated
aluminium

Colours

COD.B

ON REQ.

BEN / MEDIUM PG

PG diffuser with frosted Acryl-Satiné and impact resistant diffuser UGR<22.





CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
10PG15K4	2111	10PG15K3	1963	15W	397
10PG21K4	2887	10PG21K3	2684	21W	397

BEN / MEDIUM PG DOUBLE EMISSION

PG diffuser with frosted Acryl-Satiné and impact resistant diffuser UGR<22. Direct/indirect emission.





CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
10DI24PGK4	3733	10DI24PGK3	3493	24W: 15W+9W	397
10DI30PGK4	4509	10DI30PGK3	4214	30W: 21W+9W	397

CE · C · RETILAP · 5 YEARS WARRANTY · ETL Intertek · IP 40 · -20° +35° · CRI>90 · MacAdam 3 · RG0/RG1 · L90/B10 50.000h

On req.: DALI CODE — D · BT · 1 h EM · 1h DEM · 3 h EM · DEM · EM3H · RHL ESSE-CI · CODE K27 2700K

Body: Epoxy powder coated aluminium

Colours: COD.B · + ON REQ.

BEN / LARGE PG

PG diffuser with frosted Acryl-Satiné and impact resistant diffuser UGR<22.





CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
10PG58K4	8072	10PG58K3	7507	58W	620
10PG96K4	12710	10PG96K3	11820	96W	620

BEN / LARGE PG DOUBLE EMISSION

PG diffuser with frosted Acryl-Satiné and impact resistant diffuser UGR<22. Direct/indirect emission.





CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
10DI82PGK4	11285	10DI82PGK3	10536	82W: 58W+24W	620
10DI120PGK4	15923	10DI120PGK3	14849	120W: 96W+24W	620

CE · C · RETILAP · 5 YEARS WARRANTY · ETL Intertek · IP 40 · -20° +35° · CRI>90 · MacAdam 3 · RG0/RG1 · L90/B10 50.000h

On req.: DALI CODE — D · BT · 1 h EM · 1h DEM · 3 h EM · DEM · EM3H · RHL ESSE-CI · CODE K27 2700K

Body: Epoxy powder coated aluminium

Colours: COD.B · + ON REQ.

BEN / XL PG

PG diffuser with frosted Acryl-Satiné and impact resistant diffuser UGR<22.





CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
10PG70K4	9564	10PG70K3	8895	70W	850
10PG150K4	20550	10PG150K3	19111	150W	850

BEN / XL PG DOUBLE EMISSION

PG diffuser with frosted Acryl-Satiné and impact resistant diffuser UGR<22. Direct/indirect emission.





CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
10DI100PGK4	13580	10DI100PGK3	12681	100W: 70W+30W	850
10DI180PGK4	24566	10DI180PGK3	22897	180W: 150W+30W	850

CE · C · RETILAP · 5 YEARS WARRANTY · ETL Intertek · IP 40 · -20° +35° · CRI>90 · MacAdam 3 · RG0/RG1 · L90/B10 50.000h

On req.: DALI CODE — D · BT · 1 h EM · 1h DEM · 3 h EM · DEM · EM3H · RHL ESSE-CI · CODE K27 2700K

Body: Epoxy powder coated aluminium

Colours: COD.B · + ON REQ.

BEN / MAXI PG

PG diffuser with frosted Acryl-Satiné and impact resistant diffuser UGR<22.





CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
10PG125K4	16496	10PG125K3	15341	125W	1080
10PG185K4	24420	10PG185K3	22711	185W	1080

SUSPENDED CEILING

BEN / MAXI PG DOUBLE EMISSION

PG diffuser with frosted Acryl-Satiné and impact resistant diffuser UGR<22. Direct/indirect emission.





CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
10DI161PGK4	21316	10DI161PGK3	19885	161W: 125W+36W	1080
10DI221PGK4	29240	10DI221PGK3	27255	221W: 185W+36W	1080

CE · C · RETILAP · 5 YEARS WARRANTY · ETL Intertek · IP 40 · -20° +35° · CRI>90 · MacAdam 3 · RG0/RG1 · L90/B10 50.000h

On req.: DALI CODE — D · BT · 1 h EM · 1h DEM · 3 h EM · DEM · EM3H · RHL ESSE-CI · CODE K27 2700K

Body: Epoxy powder coated aluminium

Colours: COD.B · + ON REQ.

ACCESSORIES

DPL diffuser for IP 40 version.

10AADPLS - SMALL
10AADPLM - BEN MEDIUM
10AADPLL - BEN LARGE
10AADPLXL - BEN XL
10AADPLMX - BEN MAXI



Kit for suspended installation. Cable length 1500/3000mm.

10AA13
10AA1330



3-5 poles ceiling power supply box.
Cable length 2000mm.

00AA16 104X39XH26MM
00AA165P 104X54XH26MM



Frameless 5-pole supply box with 2000 mm cable.

00AA165PF



Kit for recessed frameless installation on plasterboard.

10AA19SF - BEN SMALL
10AA19MF - BEN MEDIUM
10AA19LF - BEN LARGE
10AA19XLF - BEN XL
10AA19MXF - BEN MAXI



Kit for recessed installation on plasterboard and concrete.

10AA19S - BEN SMALL
10AA19M - BEN MEDIUM
10AA19L - BEN LARGE