

FEATURES


 Direct emission

 UGR <22


 IP 40


LED


 3000K/4000K

 >78 lm/W

 CRI >90


 Eye safety: R60/R61


 Mac Adams 3

 L80/B10 >50.000h

CERTIFICATIONS


 EEA Conformity

 5 years warranty

 Energy efficiency

ON REQUEST

 DALI - code D*

 Bluetooth - code BT*

SPECIFICATIONS

48V DC operation.
SMD LED technology.
PG diffuser for homogeneous
emission UGR <22.

BODY

Aluminum with epoxy
powder coating.

COLORS

White RAL 9003 wrinkled
- code W
Black RAL 9005 wrinkled
- code BK

RELATED PRODUCTS

Ben suspended (P. 84)
Ben recessed (P. 124)
Ben wall (P. 249)
Ben IP54 (P. 315)

* Where available
For SWITCHDIM command use DIMTDS (pg. 337)



BEN LV

The **BEN** luminaire expands with a new **low voltage technology** component. The PG optic with satin diffuser and silk-screened perimeter and the **joint at the base** make it possible to rotate and adjust **BEN LV** to illuminate any environment in a widespread, simple and effective way.

ID 10




esse-ci

BEN LV

IP 40

Impact resistant satin polycarbonate diffuser.



Cod. 4000K		lm	L mm
10PG12K4LV	12W	931	200x210

Cod. 3000K		lm	L mm
10PG12K3LV	12W	879	200x210

TECHNICAL NOTES



BODY ROTATION

