



BRIGHT





BRIGHT's body is made of a harness holder and a light module that integrates LED and diffuser. This allows the **accessories to be fixed without any position constraint**, while the integration between LED and diffuser guarantees inaccessibility to the optical compartment. The **electrical connection** between the light module and the batters is **guaranteed by quick connectors** that prevent polarity inversions and false contacts, thus preserving the LED technology.

ID 80








esse-ci

FEATURES

-  Direct emission
-  Direct/Indirect emission
-  UGR <19; <22
-  IP 40





LED

-  3000K/4000K
- >107 lm/W icon" data-bbox="758 264 788 284"/> >107 lm/W
-  CRI >90
-  Eye safety: R60/R61
-  Mac Adams 3
-  L80/B10 >50.000h

CERTIFICATIONS

-  EEA Conformity
-  Energy efficiency
-  5 years warranty
-  ETL certification

ON REQUEST

-  DALI - code D
-  Bluetooth - code BT*
-  Emergency 1 hr - code EM*
Emergency 3 hrs - code EM3R*
-  2700K - code K27*
6500K - code K65*
-  HCL Human Centric Lighting*

SPECIFICATIONS

Built-in driver.
DPL technology for controlled emission UGR <19.
PG diffuser for homogeneous emission UGR <22.
Diffuser with ILC technology (Indirect Light Control) for partially indirect emission.

BODY

Aluminum with epoxy powder coating.

COLORS

White RAL 9003 - code B
Black RAL 9005 - code C8

* Where available


BRIGHT DPL LOW POWER

Accessories on page 32.

IP 40

Diffuser with Diamond Prism Technology UGR<19 for environments with display screen equipment. ILC (Indirect Light Control) technology for partially indirect emission.

End caps included.



Cod. 4000K	Icon	lm	L mm
80DPL12K4	12W	1310	568
80DPL18K4	18W	1966	848
80DPL24K4	24W	2621	1128
80DPL30K4	30W	3276	1408
80DPL36K4	36W	3931	1688
80DPL42K4	42W	4586	1968
80DPL48K4	48W	5242	2248
80DPL54K4	54W	5897	2528
80DPL60K4	60W	6552	2808
80DPL66K4	66W	7207	3088

Cod. 3000K	Icon	lm	L mm
80DPL12K3	12W	1219	568
80DPL18K3	18W	1828	848
80DPL24K3	24W	2437	1128
80DPL30K3	30W	3047	1408
80DPL36K3	36W	3656	1688
80DPL42K3	42W	4265	1968
80DPL48K3	48W	4875	2248
80DPL54K3	54W	5484	2528
80DPL60K3	60W	6093	2808
80DPL66K3	66W	6703	3088


BRIGHT DPL LOW POWER DOUBLE EMISSION

Accessories on page 32.

IP 40

Lower diffuser with Diamond Prism Technology UGR<19 for environments with display screen equipment. ILC (Indirect Light Control) technology and upper PG protective diffuser for dual emission: direct / indirect.

End caps included.



Cod. 4000K	Icon	lm	L mm
80DI30DPLK4	30W: 24W+6W	3221	1128
80DI36DPLK4	36W: 30W+6W	3877	1408
80DI48DPLK4	48W: 36W+12W	5119	1688
80DI54DPLK4	54W: 42W+12W	5774	1968
80DI72DPLK4	72W: 48W+24W	7617	2248
80DI78DPLK4	78W: 54W+24W	8272	2528
80DI84DPLK4	84W: 60W+24W	8927	2808
80DI90DPLK4	90W: 66W+24W	9582	3088

Cod. 3000K	Icon	lm	L mm
80DI30DPLK3	30W: 24W+6W	2996	1128
80DI36DPLK3	36W: 30W+6W	3606	1408
80DI48DPLK3	48W: 36W+12W	4761	1688
80DI54DPLK3	54W: 42W+12W	5370	1968
80DI72DPLK3	72W: 48W+24W	7084	2248
80DI78DPLK3	78W: 54W+24W	7693	2528
80DI84DPLK3	84W: 60W+24W	8302	2808
80DI90DPLK3	90W: 66W+24W	8912	3088


BRIGHT PG LOW POWER

Accessories on page 32.

IP 40

Satin methacrylate antistatic diffuser screen, UGR<22.
ILC (Indirect Light Control) technology for partially indirect emission.

End caps included.



Cod. 4000K	W	lm	L mm
80PG6K4	6W	674	288
80PG12K4	12W	1348	568
80PG18K4	18W	2022	848
80PG24K4	24W	2696	1128
80PG30K4	30W	3371	1408
80PG36K4	36W	4045	1688
80PG42K4	42W	4719	1968
80PG48K4	48W	5393	2248
80PG54K4	54W	6067	2528
80PG60K4	60W	6741	2808
80PG66K4	66W	7415	3088

Cod. 3000K	W	lm	L mm
80PG6K3	6W	627	288
80PG12K3	12W	1254	568
80PG18K3	18W	1881	848
80PG24K3	24W	2507	1128
80PG30K3	30W	3134	1408
80PG36K3	36W	3761	1688
80PG42K3	42W	4388	1968
80PG48K3	48W	5015	2248
80PG54K3	54W	5643	2528
80PG60K3	60W	6270	2808
80PG66K3	66W	6896	3088


BRIGHT DI PG LOW POWER DOUBLE EMISSION

Accessories on page 32.

IP 40

Lower satin methacrylate antistatic diffuser screen, UGR<22.
ILC (Indirect Light Control) technology and upper PG protective diffuser for dual emission: direct / indirect.

End caps included.



Cod. 4000K	W	lm	L mm
80DI30PGK4	30W: 24W+6W	3297	1128
80DI36PGK4	36W: 30W+6W	3971	1408
80DI48PGK4	48W: 36W+12W	5232	1688
80DI54PGK4	54W: 42W+12W	5906	1968
80DI72PGK4	72W: 48W+24W	7768	2248
80DI78PGK4	78W: 54W+24W	8442	2528
80DI84PGK4	84W: 60W+24W	9116	2808
80DI90PGK4	90W: 66W+24W	9790	3088

Cod. 3000K	W	lm	L mm
80DI30PGK3	30W: 24W+6W	3066	1128
80DI36PGK3	36W: 30W+6W	3693	1408
80DI48PGK3	48W: 36W+12W	4866	1688
80DI54PGK3	54W: 42W+12W	5493	1968
80DI72PGK3	72W: 48W+24W	7224	2248
80DI78PGK3	78W: 54W+24W	7852	2528
80DI84PGK3	84W: 60W+24W	8479	2808
80DI90PGK3	90W: 66W+24W	9106	3088

BRIGHT PG HIGH POWER

Accessories on page 32.

IP 40

Antistatic satin methacrylate diffuser screen, UGR <22.
Diffuser with ILC (Indirect Light Control) technology for partially indirect emission.

End caps included.



Cod. 4000K		lm	L mm
80PG48K4HP	48W	5393	1128
80PG60K4HP	60W	6741	1408
80PG72K4HP	72W	8089	1688

Cod. 3000K		lm	L mm
80PG48K3HP	48W	5015	1128
80PG60K3HP	60W	6270	1408
80PG72K3HP	72W	7523	1688

ACCESSORIES



Single wire adjustable suspension kit.
Length: 1500 / 3000mm.

80AA13
80AA1330



3 - 5 poles ceiling power box.
Cable length 2000mm.

00AA16
00AA165P



Electrified linear joint.

80AA11



2 ways electrified joint.
(Dim: 60 x 60mm)

80AA05



3 ways electrified joint.
(Dim: 60 x 81,6mm)

80AA06



4 ways electrified joint.
(Dim: 81, 6 x 81,6mm)

80AA07



Blind connection module in aluminium. Linear mechanical joints included. Other lengths on request.

80MC1000: 1000mm
80MC2000: 2000mm



End caps kit for recessed installation.

80AAPIL



Side recessing aluminum profile, also for continuous-row. Each item code is composed of 2 pieces of aluminum profile, joint plates and spacers for alignment. Stirrup brackets magnetically hold the Bright module into the profile for a trimless effect.

80PL24 - 24W(LP) / 48W(HP)
80PL30 - 30W(LP) / 60W(HP)
80PL36 - 36W(LP) / 72W(HP)
80PL42 - 42W(LP)
80PL48 - 48W(LP)
80PL54 - 54W(LP)
80PL60 - 60W(LP)
80PL66 - 66W(LP)



Kit for wall installation.

80AA15



Kit for wall installation.
Bright 6W / 12W.

80AA151M