

CUBE MINI

ID 49

CUBE MINI belongs to a range of **small-sized luminaires for both recessed and ceiling applications**.

The innovative joint system allows to break down any installation scheme, satisfying the architectural needs of any project. The body cut-off eliminates the perception of glare and improves **visual comfort**.

☑ Features

- Direct emission
- UGR<19; <22
- IP 40

💡 Led

- 3000K/4000K
- CRI>90
- Eye safety: RG0/RGI
- Mac Adams 3
- L80/B10 >50.000h

🕒 Specifications

- Satin PC primary screen, UGR<19
- PG version with additional coplanar screen in opaline PC, UGR<22

📦 Body

- Die-cast aluminium

🎨 Colors

- White RAL 9003 matte - code B
- Black RAL 9005 matte - code C8

☆ Certifications

- CE Conformity
- BIS Conformity
- RETILAP Conformity
- Energy efficiency F
- 5 years warranty

📦 On request

- DALI - code D*
- Bluetooth - code BT*
- Emergency 1 hr - code EM
- Emergency 3 hrs - code EM3H*

* Where available



CUBE MINI RECESSED

Primary diffuser in frosted PC, UGR<19.




IP 40

Cod. 4000K	Led	lm	Lmm
49DR5K4	5W	304	50
49DR8K4	8W	487	50

Cod. 3000K	Led	lm	Lmm
49DR5K3	5W	278	50
49DR8K3	8W	442	50

CUBE MINI CEILING

Primary diffuser in frosted PC, UGR<19.



IP 40

Cod. 4000K	Led	lm	Lmm
49DR5K4C	5W	304	50
49DR8K4C	8W	487	50

Cod. 3000K	Led	lm	Lmm
49DR5K3C	5W	278	50
49DR8K3C	8W	442	50

ACCESSORIES



Additional coplanar screen
in opaline PC, UGR<22.

49AAPG



Bracket for multiple
recessed installation.

49AA11

TECHNICAL NOTES

MULTIPLE INSTALLATION

