










## FEATURES

-  Direct emission
-  UGR <22
-  IP 54





## LED

-  3000K/4000K
-  >102 lm/W
-  CRI >90
-  Eye safety: R60/R61
-  Mac Adams 3
-  L80/B10 >50.000h

## CERTIFICATIONS

-  EEA Conformity
-  Energy efficiency
-  5 years warranty

## ON REQUEST

-  DALI - code D
-  Bluetooth - code BT\*
-  Emergency 1 hr - code EM  
Emergency 3 hrs - code EM3H\*
-  2700K - code K27\*  
5000K - code K5\*

## SPECIFICATIONS

Built-in driver.  
Diffuser in antistatic satin methacrylate, for homogeneous emission UGR <22.

## BODY

Aluminum with epoxy powder coating.

## COLORS

Matte white RAL 9003 - code B  
Matte black RAL 9005 - code C8

## RELATED PRODUCTS

Groove (P. 33)  
Groove Display (P. 76)  
Groove IP54 (P. 268)  
Groove Display IP54 (P. 271)

\* Where available



**GROOVE DISPLAY IP54** is designed specifically for **recessed applications** that demand **high ingress protection** against dust and moisture. Perfectly complementing the interior GROOVE collection, it can be installed either as a **single luminaire or in continuous rows**, allowing designers to freely create stunning solutions. The aluminum body and the flexible diffuser with coextruded gaskets guarantee **maximum performance**, achieving an **IP54 protection rating**, making the collection ideal for **industrial and commercial applications**, even in protected outdoors.

ID 43



# GROOVE DISPLAY IP54 LOW POWER


IP 54

Direct recessed emission.

Antistatic satin methacrylate diffuser screen for UGR <22

homogeneous emission to be ordered separately.

End-caps not included.



Cod. 4000K	W	lm	L mm
43AA24K4F54	24W	2558	1130
43AA30K4F54	30W	3197	1410
43AA36K4F54	36W	3837	1690
43AA42K4F54	42W	4476	1970
43AA48K4F54	48W	5116	2250
43AA54K4F54	54W	5755	2530
43AA60K4F54	60W	6395	2810
43AA66K4F54	66W	7034	3090

Cod. 3000K	W	lm	L mm
43AA24K3F54	24W	2381	1130
43AA30K3F54	30W	2977	1410
43AA36K3F54	36W	3572	1690
43AA42K3F54	42W	4167	1970
43AA48K3F54	48W	4763	2250
43AA54K3F54	54W	5358	2530
43AA60K3F54	60W	5954	2810
43AA66K3F54	66W	6549	3090

# GROOVE DISPLAY IP54 HIGH POWER


IP 54

Direct recessed emission.

Antistatic satin methacrylate diffuser screen for UGR <22

homogeneous emission to be ordered separately.

End-caps not included.



Cod. 4000K	W	lm	L mm
43AA45K4HPF54	45W	4706	1130
43AA57K4HPF54	57W	5961	1410
43AA68K4HPF54	68W	7112	1690

Cod. 3000K	W	lm	L mm
43AA45K3HPF54	45W	4381	1130
43AA57K3HPF54	57W	5548	1410
43AA68K3HPF54	68W	6619	1690

# ACCESSORIES



End caps kit.  
(Consider + 15 mm on the cutting length).

**43AA09F54**



PG screen for single installation.

- 43PG24** - 24W (LP) / 45W (HP)
- 43PG30** - 30W (LP) / 57W (HP)
- 43PG36** - 36W (LP) / 68W (HP)
- 43PG42** - 42W (LP)
- 43PG48** - 48W (LP)
- 43PG54** - 54W (LP)
- 43PG60** - 60W (LP)
- 43PG66** - 66W (LP)



Methacrylate satin diffuser  
UGR<22, 10m coil to be measured and cut on site to provide continuous gap-free light diffusion.

**43PG10000**



Linear joint with gasket.  
(Consider + 4 mm on the cutting length)

**43AA11F54**