

# GROOVE DISPLAY

**GROOVE DISPLAY** is the technical solution adopted for an **easy and precise installation**. It is an easy-to-manage lighting system, from the design stage to the installation of the product in continuous rows. The ideal fixture for recessed mounting on plasterboard and slatted ceilings.

ID 43



## FEATURES

-  Direct emission
-  UGR <19
-  IP 40

## LED

-  3000K/4000K
-  >105 lm/W
-  CRI >90
-  Eye safety: RG0/RG1
-  Mac Adams 3
-  L80/B10 >50.000h

## CERTIFICATIONS

-  EEA Conformity
-  Energy efficiency
-  5 years warranty

## ON REQUEST

-  DALI - code D
-  Bluetooth - code BT\*
-  Emergency 1 hr - code EM
-  Emergency 3 hrs - code EM3R\*
-  2700K - code K27\*
-  5000K - code K5\*
-  Human Centric Lighting\*

## SPECIFICATIONS

Built-in driver.  
Diffuser with DPL UGR <19 technology for environments with video terminal.

## BODY

Aluminum with epoxy powder coating.

## COLORS

Matte white RAL 9003 - code B  
Matte black RAL 9005 - code C8

## RELATED PRODUCTS

Groove (P. 33)  
Groove IP54 (P. 268)  
Groove Display IP54 (P. 271)


## GROOVE DISPLAY LOW POWER

Accessories on page 78.

IP 40

Diffuser with Diamond Prism LED technology (UGR <19)  
for environments with display screen equipment.

End caps not included.



| Cod. 4000K |  | lm   | L mm |
|------------|-----------------------------------------------------------------------------------|------|------|
| 43DPL24K4F | 24W                                                                               | 2646 | 1130 |
| 43DPL30K4F | 30W                                                                               | 3308 | 1410 |
| 43DPL36K4F | 36W                                                                               | 3969 | 1690 |
| 43DPL42K4F | 42W                                                                               | 4631 | 1970 |
| 43DPL48K4F | 48W                                                                               | 5292 | 2250 |
| 43DPL54K4F | 54W                                                                               | 5954 | 2530 |
| 43DPL60K4F | 60W                                                                               | 6615 | 2810 |
| 43DPL66K4F | 66W                                                                               | 7277 | 3090 |

| Cod. 3000K |  | lm   | L mm |
|------------|-------------------------------------------------------------------------------------|------|------|
| 43DPL24K3F | 24W                                                                                 | 2460 | 1130 |
| 43DPL30K3F | 30W                                                                                 | 3077 | 1410 |
| 43DPL36K3F | 36W                                                                                 | 3691 | 1690 |
| 43DPL42K3F | 42W                                                                                 | 4306 | 1970 |
| 43DPL48K3F | 48W                                                                                 | 4921 | 2250 |
| 43DPL54K3F | 54W                                                                                 | 5537 | 2530 |
| 43DPL60K3F | 60W                                                                                 | 6152 | 2810 |
| 43DPL66K3F | 66W                                                                                 | 6767 | 3090 |


## GROOVE DISPLAY HIGH POWER

Accessories on page 78.

IP 40

Diffuser with Diamond Prism LED technology (UGR <19)  
for environments with display screen equipment.

End caps not included.



| Cod. 4000K   |  | lm   | L mm |
|--------------|-------------------------------------------------------------------------------------|------|------|
| 43DPL45K4HPF | 45W                                                                                 | 4961 | 1130 |
| 43DPL57K4HPF | 57W                                                                                 | 6284 | 1410 |
| 43DPL68K4HPF | 68W                                                                                 | 7497 | 1690 |

| Cod. 3000K   |  | lm   | L mm |
|--------------|---------------------------------------------------------------------------------------|------|------|
| 43DPL45K3HPF | 45W                                                                                   | 4614 | 1130 |
| 43DPL57K3HPF | 57W                                                                                   | 5844 | 1410 |
| 43DPL68K3HPF | 68W                                                                                   | 6972 | 1690 |

# ACCESSORIES



End caps kit.  
(Consider + 4 mm on  
the cutting length).

**43AA09F**



Linear joint.

**43AA11F**



PG screen(UGR <22)  
in 10 m roll to be cut to  
measure for continuous  
lines without interruptions.

**43PG10000**