

HALL LED CEILING EVO PC

ID 28



HALL LED CEILING EVO PC



CE

RoHS

RETI LAP

5 YEARS WARRANTY

IP 44

CRI>90

Mac Adams 3

IK 06

RG0/RG1

L90/B10 50.000h

Body

Epoxy powder coated aluminium

-20°
+35°

HALL LED CEILING EVO PC / MINI


Clear protective glass with internal polycarbonate lens.
Beam angle: 15°-24°-36°-50°. Cut-off >30°.



CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
28PC9K415	1113	28PC9K315	939	9W 15°	60
28PC9K424	1113	28PC9K324	939	9W 24°	60
28PC9K436	1113	28PC9K336	939	9W 36°	60
28PC9K450	1113	28PC9K350	939	9W 50°	60

HALL LED CEILING EVO PC / SMALL

Clear protective glass with internal polycarbonate lens.
Beam angle: 15°-24°-36°-50°. Cut-off >30°.



CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
28PC13K415S	1451	28PC13K315S	1391	13W 15°	80
28PC13K424S	1451	28PC13K324S	1391	13W 24°	80
28PC13K436S	1451	28PC13K336S	1391	13W 36°	80
28PC13K450S	1451	28PC13K350S	1391	13W 50°	80
28PC18K415S	2009	28PC18K315S	1928	18W 15°	80
28PC18K424S	2009	28PC18K324S	1928	18W 24°	80
28PC18K436S	2009	28PC18K336S	1928	18W 36°	80
28PC18K450S	2009	28PC18K350S	1928	18W 50°	80

CE

RoHS

RETI LAP

5 YEARS WARRANTY

IP 44

CRI>90

Mac Adams 3

IK 06

RG0/RG1

L90/B10 50.000h

On req.:

CODE K27 2700K

CODE K5 5000K

Body

Epoxy powder coated aluminium

-20°
+35°

Colours


COD.W

COD.BK

ONREQ.

HALL LED CEILING EVO PC / MEDIUM

Clear protective glass with internal polycarbonate lens.
Beam angles: 15°–24°–36°–50°–70°. Cut-off >30°.




CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
28PC18K415M	2250	28PC18K315M	2106	18W 15°	110
28PC18K424M	2250	28PC18K324M	2106	18W 24°	110
28PC18K436M	2250	28PC18K336M	2106	18W 36°	110
28PC18K450M	2250	28PC18K350M	2106	18W 50°	110
28PC18K470M	2250	28PC18K370M	2106	18W 70°	110
28PC25K415M	3130	28PC25K315M	2926	25W 15°	110
28PC25K424M	3130	28PC25K324M	2926	25W 24°	110
28PC25K436M	3130	28PC25K336M	2926	25W 36°	110
28PC25K450M	3130	28PC25K350M	2926	25W 50°	110
28PC25K470M	3130	28PC25K370M	2926	25W 70°	110



HALL LED CEILING EVO PC / LARGE

Clear protective glass with internal polycarbonate lens.
Beam angles: 15°–24°–36°–50°–70°. Cut-off >30°.



CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
28PC35K415L	4029	28PC35K315L	3897	35W 15°	150
28PC35K424L	4029	28PC35K324L	3897	35W 24°	150
28PC35K436L	4029	28PC35K336L	3897	35W 36°	150
28PC35K450L	4029	28PC35K350L	3897	35W 50°	150
28PC35K470L	4029	28PC35K370L	3897	35W 70°	150
28PC38K415L	4214	28PC38K315L	4100	38W 15°	150
28PC38K424L	4214	28PC38K324L	4100	38W 24°	150
28PC38K436L	4214	28PC38K336L	4100	38W 36°	150
28PC38K450L	4214	28PC38K350L	4100	38W 50°	150
28PC38K470L	4214	28PC38K370L	4100	38W 70°	150
28PC50K415L	5483	28PC50K315L	5125	52W 15°	150
28PC50K424L	5483	28PC50K324L	5125	52W 24°	150
28PC50K436L	5483	28PC50K336L	5125	52W 36°	150
28PC50K450L	5483	28PC50K350L	5125	52W 50°	150
28PC50K470L	5483	28PC50K370L	5125	52W 70°	150



CE

RETI LAP

5 YEARS WARRANTY

IP 44

CRI>90

Mac Adams 3

IK 06

RG0/RG1

L90/B10 50.000h

On req.: DALI CODE - D

BT

CODE K27 2700K

CODE K5 5000K

Body

Epoxy powder coated aluminium

Colours

COD.W

COD.BK

ON REQ.

-20°

+35°

ACCESSORIES



Wire suspension kit with 3 pole-powered supply box. Cable length: 3000mm.

28AA16MNE - MINI
28AA16SE - SMALL
28AA16ME - MEDIUM
28AA16LE - LARGE



Wire suspension kit with 5 pole-powered supply box. Cable length: 3000mm.

28AA165PMNE - MINI
28AA165PSE - SMALL
28AA165PME - MEDIUM
28AA165PLE - LARGE



Frosted glass with gasket.

28AAVSMN - MINI
28AAVSS - SMALL
28AAVSM - MEDIUM
28AAVSL - LARGE

ANTI-GLARE RINGS

Anti-glare rings that allow to focus the light beam hiding the light source. They perfectly fit in art galleries, museums and retail areas to value the subject with accent light without annoying glare issues - UGR<16.



28AA60AGW - MINI
Internal/external color: White RAL 9003.

28AA60AGWBK - MINI
Internal color: Black RAL 9005.
External color: White RAL 9003.

28AA60AGBK - MINI
Internal/external color: Black RAL 9005.



28AA80SAGW - SMALL
Internal/external color: White RAL 9003.

28AA80SAGWBK - SMALL
Internal color: Black RAL 9005.
External color: White RAL 9003.

28AA80SAGBK - SMALL
Internal/external color: Black RAL 9005.



28AA110MAGW - MEDIUM
Internal/external color: White RAL 9003.

28AA110MAGWBK - MEDIUM
Internal color: Black RAL 9005.
External color: White RAL 9003.

28AA110MAGBK - MEDIUM
Internal/external color: Black RAL 9005.