

HALL LED CEILING IP65 PC

ID 28



HALL LED CEILING
IP65 PC



CE

ED

5 YEARS WARRANTY

IP65

CRI>90

Mac Adams 3

IK 06

RG0/RG1

L90/B10
50.000h


-20°
+45°

Corpo

Alluminio
pressofuso

HALL LED CEILING IP65 / MINI PC


Vetro trasparente di protezione con lente interna in policarbonato.
Fascio: 15°-24°-36°-50°. Cut-off>30°.



CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
28PC9K41565	1113	28PC9K31565	939	9W 15°	60
28PC9K42465	1113	28PC9K32465	939	9W 24°	60
28PC9K43665	1113	28PC9K33665	939	9W 36°	60
28PC9K45065	1113	28PC9K35065	939	9W 50°	60

HALL LED CEILING IP65 / SMALL PC

Vetro trasparente di protezione con lente interna in policarbonato.
Fascio: 15°-24°-36°-50°. Cut-off>30°.



CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
28PC13K415S65	1451	28PC13K315S65	1391	13W 15°	80
28PC13K424S65	1451	28PC13K324S65	1391	13W 24°	80
28PC13K436S65	1451	28PC13K336S65	1391	13W 36°	80
28PC13K450S65	1451	28PC13K350S65	1391	13W 50°	80
28PC18K415S65	2009	28PC18K315S65	1928	18W 15°	80
28PC18K424S65	2009	28PC18K324S65	1928	18W 24°	80
28PC18K436S65	2009	28PC18K336S65	1928	18W 36°	80
28PC18K450S65	2009	28PC18K350S65	1928	18W 50°	80

CE

ED

5 YEARS WARRANTY

IP65

CRI>90

Mac Adams 3

IK 06

RG0/RG1

L90/B10
50.000h

-20°
+45°

On req.:

CODE - D

MINI
Ø 60

CODE K27
2700K

CODE K5
5000K

Corpo

Alluminio
pressofuso

Cromie

COD.W


COD.BK

ONREQ.

HALL LED CEILING IP65 / MEDIUM PC

Vetro trasparente di protezione con lente interna in policarbonato.

Fascio: 15°-24°-36°-50°-70°. Cut-off>30°.



CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
28PC18K415M65	2250	28PC18K315M65	2106	18W 15°	110
28PC18K424M65	2250	28PC18K324M65	2106	18W 24°	110
28PC18K436M65	2250	28PC18K336M65	2106	18W 36°	110
28PC18K450M65	2250	28PC18K350M65	2106	18W 50°	110
28PC18K470M65	2250	28PC18K370M65	2106	18W 70°	110
28PC25K415M65	3130	28PC25K315M65	2926	25W 15°	110
28PC25K424M65	3130	28PC25K324M65	2926	25W 24°	110
28PC25K436M65	3130	28PC25K336M65	2926	25W 36°	110
28PC25K450M65	3130	28PC25K350M65	2926	25W 50°	110
28PC25K470M65	3130	28PC25K370M65	2926	25W 70°	110



ACCESSORI




Vetro satinato con guarnizione.

28AAVSMN - MINI
28AAVSS - SMALL
28AAVSM - MEDIUM
28AAVSL - LARGE

HALL LED CEILING IP65 / LARGE PC

Vetro trasparente di protezione con lente interna in policarbonato.

Fascio: 15°-24°-36°-50°-70°. Cut-off>30°.



CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
28PC35K415L65	4029	28PC35K315L65	3897	35W 15°	150
28PC35K424L65	4029	28PC35K324L65	3897	35W 24°	150
28PC35K436L65	4029	28PC35K336L65	3897	35W 36°	150
28PC35K450L65	4029	28PC35K350L65	3897	35W 50°	150
28PC35K470L65	4029	28PC35K370L65	3897	35W 70°	150
28PC38K415L65	4214	28PC38K315L65	4100	38W 15°	150
28PC38K424L65	4214	28PC38K324L65	4100	38W 24°	150
28PC38K436L65	4214	28PC38K336L65	4100	38W 36°	150
28PC38K450L65	4214	28PC38K350L65	4100	38W 50°	150
28PC38K470L65	4214	28PC38K370L65	4100	38W 70°	150
28PC50K415L65	5483	28PC50K315L65	5125	50W 15°	150
28PC50K424L65	5483	28PC50K324L65	5125	50W 24°	150
28PC50K436L65	5483	28PC50K336L65	5125	50W 36°	150
28PC50K450L65	5483	28PC50K350L65	5125	50W 50°	150
28PC50K470L65	5483	28PC50K370L65	5125	50W 70°	150



CE

ED

5 YEARS WARRANTY

IP 65

CRI>90

Mac Adams 3

IK 06

RG0/RG1

L90/B10 50.000h

On req.:
RAI
CODE — D

MINI
Ø 60

CODE K27
2700K

CODE K5
5000K

Corpo

Alluminio pressofuso

Cromie

COD.W

COD.BK

ONREQ.

° -20°
° +45°