HALL LED IP67

ID 38






HALL LED IP67
ACCENT LIGHT



HALL LED IP67
DIFFUSED LIGHT



HALL LED IP67
WALL WASHER



CEILING



GROUND



WALL

CE | F | E mini | 5 YEARS WARRANTY | RETILAP

IP 67 | CRI>90 | MacAdam 3 | IK 10 | RG0/RG1 | L90/B10 50.000h | -20° +55°* | working load max 510 kg | 24V | corrosion proof C5-L

Body

AISI 316
stainless
steel

HALL LED IP67 / PICO ACCENT LIGHT

Transparent glass with PC lens beam angle 16°-24°-36°.
1000mm cable with connector. Without driver.






CCT. 3000K	lm	Led	Ømm
38AL1K316	85	1W 16°	25
38AL1K324	85	1W 24°	25
38AL1K336	85	1W 36°	25

HALL LED IP67 / MICRO ACCENT LIGHT

Transparent glass with PC lens beam angle 16°-24°-36°-50°.
1000mm cable with connector. Without driver.





CCT. 3000K	lm	Led	Ømm
38AL3K316	280	3W 16°	45
38AL3K324	280	3W 24°	45
38AL3K336	280	3W 36°	45
38AL3K350	280	3W 50°	45

HALL LED IP67 / PICO DIFFUSED LIGHT

Matt glass for diffused light.
1000mm cable with connector. Without driver.





CCT. 3000K	lm	Led	Ømm
38VS1K3	80	1W	25

CE | F | E mini | 5 YEARS WARRANTY | RETILAP

IP 67 | CRI>90 | MacAdam 3 | IK 10 | RG0/RG1 | L90/B10 50.000h | -20° +55°* | working load max 510 kg | 24V | corrosion proof C5-L

On req.:
DALI
CODE — D

CODE K4
4000K

Body

AISI 316
stainless
steel

Colours

AISI 316

HALL LED IP67 / MICRO DIFFUSED LIGHT

Matt glass for diffused light.
1000mm cable with connector. Without driver.






CCT. 3000K	lm	Led	Ømm
38VS3K3	275	3W	45

HALL LED IP67 / MICRO WALL WASHER

Matt glass for asymmetrical light.
1000mm cable with connector. Without driver.







CCT. 3000K	lm	Led	Ømm
38WW2K3	270	2W	45

TECHNICAL NOTES

Internal glue filled for complete water-proof and anti-condensation.





CE · F · E mini
5 YEARS WARRANTY · RETILAP

IP 67 · CRI>90 · MacAdam 3
IK 10 · RG0/RG1 · L90/B10 50.000h
-20° +55°* · working load max 510 kg · 24V · corrosion proof C5-L

On req.: DALI CODE — D · CODE K4 4000K

Body: AISI 316 stainless steel
Colours: AISI 316

HALL LED IP67 / MINI ACCENT LIGHT

Clear glass and PC lens, 16°–24°–36°–50°, and 4° HIGH NARROW BEAM.
1000 mm cable with connector. Driver not included.





PC LENS VERSION

CCT. 3000K	lm	Led	Ømm
38AL7K316	470	7W 16°	65
38AL7K324	470	7W 24°	65
38AL7K336	470	7W 36°	65
38AL7K350	470	7W 50°	65

HIGH NARROW BEAM 4° LENS VERSION

CCT. 3000K	lm	Led	Ømm
38HNB2K3	130	2W 4°	65

ACCESSORIES



Cable with double connector length 500/ 2000/4000/8000mm.

38AACA500
38AACA2000
38AACA4000
38AACA8000



T-Connector with cable with one end of 1000mm and two of 500mm.

38AACA06



4x output distribution connectors with 1000mm cable.

38AACA4XDC



8x output distribution connectors with 1000mm cable.

38AACA8XDC



End cap connector.

38AA09CATP



Recessed box for installation on the ground or on concrete.

38AA17PK - PICO
38AA17MK - MICRO
38AA17MN - MINI



24V IP67 driver box with output connector and integrated driver.

38BX1267 12W
38BX2067 20W
38BX3067 30W



Oversized frame for 68 mm recessed cut-out.

38FR74MN - MINI