

HALL LED IP66

ID 38

HALL LED IP66 is a series of outdoor LED downlights for **functional and architectural lighting**, which puts structures in the foreground while staying behind the scenes: thanks to the **built-in driver**, it always manages to offer **elegant** and **compact** solutions.

☑ Features

- Direct emission
- IP 66
- IK 06
- -20°/+40°

💡 Led

- 3000K/4000K
- >90 lm/W; >126 lm/W
- CRI>90
- Eye safety: RG0/RG1
- Mac Adams 3
- L80/B10 >50.000h

🕒 Specifications

- Built-in driver
- CoB LED technology
- MEDIUM AND LARGE: internal reflectors aluminum with emissions: 10°-12°-20°-40°-70°-80°
- ACCENT LIGHT: concentrated beam
- High Wall Washer
- Wide Wall Washer

📏 Body

- Die-cast aluminum

🎨 Colors

- White RAL 9003 wrinkled - code B
- Black RAL 9005 wrinkled - code C8

★ Certifications

- CE Conformity
- Energy efficiency D
- 5 years warranty

📦 On request

- DALI - code D*
- Emergency 1 hr - code EM*
- Emergency 3 hrs - code EM3H*
- 5000K - code K5*

** Where available*



HALL LED IP66 MEDIUM

Internal aluminum reflectors.

Beam angles: 10°-20°-40°-70°. Cut-off>30°.



Cod. 4000K	Led	lm	Ømm
38VT7K410M66	7W 10°	655	165
38VT7K420M66	7W 20°	655	165
38VT7K440M66	7W 40°	655	165
38VT7K470M66	7W 70°	655	165
38VT18K410M66	18W 10°	1595	165
38VT18K420M66	18W 20°	1595	165
38VT18K440M66	18W 40°	1595	165
38VT18K470M66	18W 70°	1595	165

Cod. 3000K	Led	lm	Ømm
38VT7K310M66	7W 10°	627	165
38VT7K320M66	7W 20°	627	165
38VT7K340M66	7W 40°	627	165
38VT7K370M66	7W 70°	627	165
38VT18K310M66	18W 10°	1529	165
38VT18K320M66	18W 20°	1529	165
38VT18K340M66	18W 40°	1529	165
38VT18K370M66	18W 70°	1529	165

HALL LED IP66 MEDIUM ACCENT LIGHT

AL - Accent Light (concentrating beam).

Transparent glass with internal aluminum reflectors.

Beam angles: 25°-45°-60°-80°. Cut-off>30°.




Cod. 4000K	Led	lm	Ømm
38AL13K425M66	13W 25°	1326	165
38AL13K445M66	13W 45°	1326	165
38AL13K460M66	13W 60°	1326	165
38AL13K480M66	13W 80°	1326	165

Cod. 3000K	Led	lm	Ømm
38AL13K325M66	13W 25°	1207	165
38AL13K345M66	13W 45°	1207	165
38AL13K360M66	13W 60°	1207	165
38AL13K380M66	13W 80°	1207	165

HALL LED IP66 MEDIUM HIGH WALL WASHER

HW - High Wall Washer. Transparent glass with high asymmetric lens. Cut-off >30°.




Cod. 4000K	Led	lm	Ømm
38HA13K4M66	13W	1326	165

Cod. 3000K	Led	lm	Ømm
38HA13K3M66	13W	1207	165

HALL LED IP66 MEDIUM WIDE WALL WASHER

WW - Wide Wall Washer. Transparent glass with wide beam asymmetric lens. Cut-off >30°.



Cod. 4000K	Led	lm	Ømm
38WA13K4M66	13W	1326	165

Cod. 3000K	Led	lm	Ømm
38WA13K3M66	13W	1207	165

HALL LED IP66 LARGE

Internal aluminum reflectors: beam angles: 12°-20°-40°-70°.
Cut-off>30°.



Cod. 4000K	Led	lm	Ømm
38VT18K412L66	18W 12°	2316	220
38VT18K420L66	18W 20°	2316	220
38VT18K440L66	18W 40°	2316	220
38VT18K470L66	18W 70°	2316	220
38VT25K412L66	25W 12°	3151	220
38VT25K420L66	25W 20°	3151	220
38VT25K440L66	25W 40°	3151	220
38VT25K470L66	25W 70°	3151	220

Cod. 3000K	Led	lm	Ømm
38VT18K312L66	18W 12°	2240	220
38VT18K320L66	18W 20°	2240	220
38VT18K340L66	18W 40°	2240	220
38VT18K370L66	18W 70°	2240	220
38VT25K312L66	25W 12°	3048	220
38VT25K320L66	25W 20°	3048	220
38VT25K340L66	25W 40°	3048	220
38VT25K370L66	25W 70°	3048	220

ACCESSORIES



HALL LED IP65 MEDIUM
Box for recessed installation
on concrete.

38AABCM



HALL LED IP65 LARGE
Box for recessed installation
on concrete.

38AABCL