

TRILLY

ID 01

A compact, precise, and rigorous suspension, designed to deliver **high-level optical performance within an elegant and discreet body**. At the heart of **TRILLY** lies a highly engineered LED module capable of housing three different optical accessories and a decorative reflector: a silicone diffuser, ensuring homogeneous and enveloping illumination; an aluminum reflector, for more direct and defined light; or a decorative reflector, which adds character through a refined play of light.

Its installation versatility allows smooth integration into any architectural context: it can be suspended individually with canopy, installed on the Ghostfeed 2.0 low-voltage system, or mounted on standard 48V tracks.

☑ Features

- Direct emission
- UGR <19
- IP 40



Led

- 2700K/3000K/4000K
- CRI>90
- Eye safety: RGO / RGiMac Adams 3
- L70/B50 >150.000h

☑ Specifications

- Direct emission with PC lens
- Silicone diffuser
- Aluminum reflector
- Decorative reflector in thermoformed wadding

☐ Corpo

- Die-cast aluminum

📦 A richiesta

- DALI – code D*
- Bluetooth – code BT*

🔊 Cromie

- Matte white RAL 9003 wrinkled – code W
- Matte black RAL 9005 wrinkled – code BK

☆ Certificazioni

- CE Conformity
- Energy efficiency class E
- 5 years warranty

** Where available*

TRILLY

Element for single installation with semi-transparent silicone diffuser.



IP 40

Cod. 4000K	Led	lm	ø mm
01DSL3K4	3W	334	100


Cod. 2700K	Led	lm	ø mm
01DSL3K27	3W	292	100



Cod. 3000K	Led	lm	ø mm
01DSL3K3	3W	310	100

TRILLY DIRECT

Element for single installation with aluminum diffuser.



IP 40

Cod. 4000K	Led	lm	ø mm
01DA3K4	3W	293	100

Cod. 2700K	Led	lm	ø mm
01DA3K27	3W	256	100




Cod. 3000K	Led	lm	ø mm
01DA3K3	3W	272	100



TRILLY_FABRIC

Element for single installation with decorative reflector in thermoformed wadding, grey with black edge.



Cod. 4000K	Led	lm	ø mm
01DD3K4	3W	364	100

Cod. 2700K	Led	lm	ø mm
01DD3K27	3W	319	100

Cod. 3000K	Led	lm	ø mm
01DD3K3	3W	340	100

ACCESSORIES



Ceiling powered supply box with 2000mm cable .

01AA16

DALI version.

01AA16D



Power supply/Suspension for Low Voltage 48V track with 2000 mm cable.

01AA16LV

DALI version.

01AA16LVD



Connection for Ghostfeed 2.0 with 2000 mm cable.

01AA16GF