

ISIB LED IP54 fixtures with back light LED technology are the perfect mix between competitiveness, performance and flexibility. Perfect homogeneous emission thanks to the frosted or microprismatic diffuser. The IP54 rating make it also suitable for environments where a high degree of protection is required. Ideal for false ceilings with exposed structure, ISIB LED IP54 can be installed also on plasterboard thanks to the dedicated accessory.

ID 34



FEATURES

ŝ	Direct emission
۲	UGR <22; <19
%	IP 54(frontalmente)
LED	
^	3000K/4000K
<u>-</u> D-	>112 lm/W
	CRI >90
60	Eye safety: RGO/RG1
	Mac Adams 3
X	L80/B10 >50.000h
CERTIF	ICATIONS
٢€	EEA Conformity
D	Energy efficiency
Q	5 years warranty
DN REQ	UEST
	DALI - code D
*	Bluetooth - code BT*
∆ ^{3h}	Emergency 1 hr - code EM Emergency 3 hrs - code EM3H*
⊞	False ceiling version 625x625mm*
Р	Ceiling mount installation kit*
\$	5000K - code K5*

SPECIFICATIONS

Built-in driver. Quick connector for easy wiring. High homogeneity satin acrylic diffuser glued to the body, UGR <22. Additional microprismatic plate applied on the structure, UGR <19.

BODY

Steel sheet with with epoxy powder coating.

COLORS

White RAL 9003

ISIB LED IP54 PG

Frosted high homogeneity acrylic diffuser glued to the body, UGR<22.





IP 54

Cod. 4000K	Ē	Im	Lmm	Cod. 3000K	Ē	Im	Lmm	
34PG34K454	34W	3952	596x596	34PG34K354	34W	3786	596x596	
34PG55K454	55W	6175	596x596	34PG55K354	55W	5558	596x596	
34PG34K4M354	34W	3952	296x1196	34PG34K3M354	34W	3786	296x1196	

ACCESSORIES



Microprismatic plate (UGR <19) for mounting on ceiling module 600 with visible structure.

LMISIMP3454 594x594mm LMISIMP34M354 294x1194mm \bigcirc

Plasterboard installation frame.

 FCG3454
 600x600mm

 FCG34M354
 300x1200mm

.....