JOOLS LV

ID 11





JOOLS LV

CE | C | RETILAP

5 YEARS WARRANTY

IP 40 | CRI>90 | MacAdam 3

-20° +35° | RG0/RG1 | L90/B10 50.000h

48 V

Body

Epoxy
powder coated
aluminium

LOW VOLTAGE

JOOLS LV

Diffused satin PC for indirect emission. Direct emission with PC lens.
Cut-off>30°. Beam angles: 14°-35°-55°.



Ø 150 / 200 / 250



With power supply box and cable length 2000mm.

CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
11DI19K414LV	1881	11DI19K314LV	1768	19W 14°: 12W+7W	150
11DI19K435LV	1881	11DI19K335LV	1768	19W 35°: 12W+7W	150
11DI19K455LV	1881	11DI19K355LV	1768	19W 55°: 12W+7W	150
11DI22K414LV	2106	11DI22K314LV	1980	22W 14°: 14W+8W	200
11DI22K435LV	2106	11DI22K335LV	1980	22W 35°: 14W+8W	200
11DI22K455LV	2106	11DI22K355LV	1980	22W 55°: 14W+8W	200
11DI27K414LV	2498	11DI27K314LV	2349	27W 14°: 17W+10W	250
11DI27K435LV	2498	11DI27K335LV	2349	27W 35°: 17W+10W	250
11DI27K455LV	2498	11DI27K355LV	2349	27W 55°: 17W+10W	250

For the version compatible with TWOS 48V track module, add "MC" to the code.

TECHNICAL NOTES

EXAMPLE OF INSTALLATION ON RECESSED LV TRACK



CE | C | RETILAP

5 YEARS WARRANTY

IP 40 | CRI>90 | MacAdam 3

-20° +35° | RG0/RG1 | L90/B10 50.000h

48 V

On req.:
DALI CODE — D | BT

RHL ESSE-CI | CODE K27 2700K | CODE K5 5000K

CODE DIMTDS SWITCHDIM

Body

Epoxy
powder coated
aluminium

Colours

COD.W | COD.BK | COD.C67

+ ON REQ.