



JOOOLS

JOOOLS is a suspension lamp with an **essential and compact shape but powerful in flow**, with bidirectional emission for **professional applications such as retail and hospitality**. With a highly decorative character, it is ideal for desks and reception areas as accent light, without sacrificing **indirect lighting for the whole environment**.

ID 11









Design
Serge & Robert Cornelissen

esse-ci

FEATURES

-  Direct/Indirect emission
-  UGR <19
-  IP 40



LED

-  3000K/4000K
-  >99 lm/W
-  CRI >90
-  Eye safety: R60/R61
-  Mac Adams 3
-  L80/B10 >50.000h

CERTIFICATIONS

-  EEA Conformity
-  Energy efficiency
-  5 years warranty

ON REQUEST

-  DALI - code D
-  2700K - code K27*
5000K - code K5*

SPECIFICATIONS

CoB LED technology.
Diffusing satin PC for indirect emission.
Direct emission with PC lens.
CUT-OFF > 30°

BODY

Aluminum with epoxy powder coating.

COLORS

White RAL 9003 - code W
Black RAL 9005 - code BK
Anodized champagne - code C67

RELATED PRODUCTS


Jools LV (P. 223)

* Where available

JOOOLS

IP 40

Indirect emission in diffusing satin PC. Direct emission with PC lens. CUT-OFF > 30°. Beam angles 14° - 35° - 55°.



SUSPENDED/CEILING

Cod. 4000K	☼	lm	Ø mm
11DI19K414	19W 14°: 12W+7W	1881	150
11DI19K435	19W 35°: 12W+7W	1881	150
11DI19K455	19W 55°: 12W+7W	1881	150
11DI22K414	22W 14°: 14W+8W	2106	200
11DI22K435	22W 35°: 14W+8W	2106	200
11DI22K455	22W 55°: 14W+8W	2106	200
11DI27K414	27W 14°: 17W+10W	2498	250
11DI27K435	27W 35°: 17W+10W	2498	250
11DI27K455	27W 55°: 17W+10W	2498	250

Cod. 3000K	☼	lm	Ø mm
11DI19K314	19W 14°: 12W+7W	1768	150
11DI19K335	19W 35°: 12W+7W	1768	150
11DI19K355	19W 55°: 12W+7W	1768	150
11DI22K314	22W 14°: 14W+8W	1980	200
11DI22K335	22W 35°: 14W+8W	1980	200
11DI22K355	22W 55°: 14W+8W	1980	200
11DI27K314	27W 14°: 17W+10W	2349	250
11DI27K335	27W 35°: 17W+10W	2349	250
11DI27K355	27W 55°: 17W+10W	2349	250

Power/suspension cable included. Requires power supply box.

ACCESSORIES



Power supply box with built-in driver, for ceiling installation.

11AA16E



Power supply box with built-in driver, for ceiling installation. DALI version.

11AA16ED



Power supply box with built-in driver, for recessed installation.

11AA16ER



Power supply box with built-in driver, for recessed installation. DALI version.

11AA16ERD