

JOOLS LV is the **elegant suspension lamp in aluminum** for application on LV track. Compact but powerful, with **double emission**, it is suitable for professional, retail and residential contexts, thanks to the **strong decorative component**.

☑ Features

- Direct/indirect emission
- UGR<19
- IP 40

💡 Led

- 3000K/4000K
- >99 lm/W
- CRI>90
- Eye safety: RG0/RGI
- Mac Adams 3
- L80/B10 >50.000h

🕒 Specifications

- CoB LED technology
- Indirect emission in diffusing satin PC
- Direct emission with PC lens.
- Cut-off>30°

📦 Body

- Aluminum with epoxy powder coating

🎨 Colors

- White RAL 9003 - code W
- Black RAL 9005 - code BK
- Anodized champagne - code C67

★ Certifications

- CE Conformity
- RETILAP Conformity
- Energy efficiency E
- 5 years warranty

⇄ Related products

- Lv Track (p. 216)

📦 On request

- DALI - code D*
- Bluetooth - code BT*
- 2700K - code K27*
- 5000K - code K5*

** Where available*


For SWITCHDIM use

DIMTDS (p. 381)



JOOLS LV

Diffused satin PC for indirect emission. Direct emission with PC lens. Cut-off >30°. Beam angles: 14°-35°-55°.



•∅ 150 / 200 / 250•



UGR<19

IP 40

With power supply box and cable length 2000mm.

Cod. 4000K	Led	lm	Ømm
11DI19K414LV	19W 14°:12W+7W	1881	150
11DI19K435LV	19W 35°:12W+7W	1881	150
11DI19K455LV	19W 55°:12W+7W	1881	150
11DI22K414LV	22W 14°:14W+8W	2106	200
11DI22K435LV	22W 35°:14W+9W	2106	200
11DI22K455LV	22W 55°:14W+9W	2106	200
11DI27K414LV	27W 14°:17W+10W	2498	250
11DI27K435LV	27W 35°:17W+10W	2498	250
11DI27K455LV	27W 55°:17W+10W	2498	250

Cod. 3000K	Led	lm	Ømm
11DI19K314LV	19W 14°:12W+7W	1768	150
11DI19K335LV	19W 35°:12W+7W	1768	150
11DI19K355LV	19W 55°:12W+7W	1768	150
11DI22K314LV	22W 14°:14W+8W	1980	200
11DI22K335LV	22W 35°:14W+9W	1980	200
11DI22K355LV	22W 55°:14W+9W	1980	200
11DI27K314LV	27W 14°:17W+10W	2349	250
11DI27K335LV	27W 35°:17W+10W	2349	250
11DI27K355LV	27W 55°:17W+10W	2349	250

TECHNICAL NOTES

EXAMPLE OF INSTALLATION ON RECESSED LV TRACK

