







FEATURES

-  Direct emission
-  UGR <22
-  IP 54
-  IK 10
-  -25° / +35°

LED

-  3000K/4000K
-  >98 lm/W; >103 lm/W
-  CRI >90
-  Eye safety: RG0/RG1
-  Mac Adams 3
-  L80/B10 >50.000h

CERTIFICATIONS

-  EEA Conformity
-  Energy efficiency
-  5 years warranty

ON REQUEST

-  DALI - code D
-  Emergency 1 hr - code EM
Emergency 3 hrs - code EM3H*
-  5000K - code K5*
6500K - code K65*

SPECIFICATIONS

Built-in driver.
Impact resistant polycarbonate diffuser.

BODY

Polycarbonate with high mechanical resistance.
Polyurethane foam seal (PUR)



LINEA IP54

LINEA IP54 is the family of fixtures that **combine efficiency and energy saving** with a long life time. Ideal for laboratories, walking areas and industrial environments.

ID 12




* Where available

esse-ci

LINEA IP54 ^{LONG}

IP 54 IK10

Impact resistant polycarbonate diffuser.




Cod. 4000K	☼	lm	L mm
12P021K454	21W	2130	109x1160
12P025K454	25W	2716	109x1160
12P033K454	33W	3506	109x1160
12P039K454	39W	3971	159x1160
12P048K454	48W	4948	159x1160
12P065K454	65W	6705	159x1160

Cod. 3000K	☼	lm	L mm
12P021K354	21W	1894	109x1160
12P025K354	25W	2255	109x1160
12P033K354	33W	2977	109x1160
12P039K354	39W	3518	159x1160
12P048K354	48W	4330	159x1160
12P065K354	65W	5864	159x1160

LINEA IP54 ^{SQUARE}

IP 54 IK10

Impact resistant polycarbonate diffuser.




Cod. 4000K	☼	lm	L mm
12P010K454	10W	1097	300
12P013K454	13W	1386	300
12P018K454	18W	1879	300
12P027K454	27W	2688	300

Cod. 3000K	☼	lm	L mm
12P010K354	10W	893	300
12P013K354	13W	1161	300
12P018K354	18W	1607	300
12P027K354	27W	2411	300

LINEA IP54 ^{ROUND}

IP 54 IK10

Impact resistant polycarbonate diffuser.




Cod. 4000K	☼	lm	Ø mm
12P010K454R	10W	1116	300
12P013K454R	13W	1395	300
12P018K454R	18W	1897	300
12P027K454R	27W	2725	300

Cod. 3000K	☼	lm	Ø mm
12P010K354R	10W	911	300
12P013K354R	13W	1185	300
12P018K354R	18W	1641	300
12P027K354R	27W	2461	300

LINEA IP54 ^{ROUND INTELLIGENT}

IP 54 IK10

Impact resistant polycarbonate diffuser. Integrated presence sensor, settable with deepswitch.



Cod. 4000K	☼	lm	Ø mm
12P010K454RS	10W	1116	300
12P013K454RS	13W	1395	300

Cod. 3000K	☼	lm	Ø mm
12P010K354RS	10W	911	300
12P013K354RS	13W	1185	300