










FEATURES

-  Direct emission
-  UGR <16; <22
-  IP40




LED

-  3000K/4000K
-  >120 lm/W
-  CRI >90
-  Eye safety: R60/R61
-  Mac Adams 3
-  L80/B10 >50.000h

CERTIFICATIONS

-  EEA Conformity
-  Energy efficiency
-  5 years warranty

ON REQUEST

-  DALI - code D*
-  Bluetooth - code BT**
-  2700K - code K27**

SPECIFICATIONS

48V DC operation.
SMD LED technology.
PG diffuser in satin methacrylate for homogeneous emission (UGR <22).
Diffuser with CLD collimated optics (UGR <16).

BODY

Anodized aluminum.

COLORS

White RAL 9003 - code B
Black RAL 9011 - code C8

RELATED PRODUCTS

LV Track (P. 184)



LUDO LINEAR 2.0 is the linear luminaire for **low voltage tracks**, dimmable and equipped with PG optics for **homogeneous emission** (UGR <22) or CLD collimated optics **with controlled emission** (UGR <16). Thanks to the quick fixing, **LUDO LINEAR 2.0** is extremely versatile and becomes ideal for the retail world or contemporary living areas.

ID 20




*Where available
For SWITCHDIM command use DIMTDS (pg. 337)

LUDO LINEAR 2.0^{PG}

IP 40

PG diffuser in satin-finished methacrylate for homogeneous emission, UGR<22.




Cod. 4000K	Icon	lm	L mm
20PG6K4	6W	708	365
20PG12K4	12W	1416	725
20PG18K4	18W	2124	1085

Cod. 3000K	Icon	lm	L mm
20PG6K3	6W	649	365
20PG12K3	12W	1298	725
20PG18K3	18W	1947	1085

LUDO LINEAR 2.0^{CLD}

IP 40

Direct emission with CLD technology, with collimated diffuser, UGR<16.



Cod. 4000K	Icon	lm	L mm
20CLD6K4	6W	616	365
20CLD12K4	12W	1232	725
20CLD18K4	18W	1848	1085

Cod. 3000K	Icon	lm	L mm
20CLD6K3	6W	565	365
20CLD12K3	12W	1129	725
20CLD18K3	18W	1694	1085