










FEATURES

-  Direct emission
-  UGR <16**; <19
-  IP 44





LED

-  3000K/4000K
-  >100 lm/W
-  CRI >90
-  Eye safety: R60/R61
-  Mac Adams 3
-  L80/B10 >50.000h

CERTIFICATIONS

-  EEA Conformity
-  Energy efficiency
-  5 years warranty

ON REQUEST

-  DALI - code D
-  Bluetooth - code BT*
-  Emergency 1 hr - code EM
Emergency 3 hrs - code EM3R*
-  2700K - code K27*
5000K - code K5*

SPECIFICATIONS

Built-in driver.
Polycarbonate lens,
beam angles: 15°, 24°, 36°, 50°.
Front reflector in polycarbonate.

BODY

Aluminum with epoxy
powder coating.

COLORS

White RAL 9003 wrinkled
- code W
Black RAL 9005 wrinkled
- code BK



MAKE R

MAKE R is the new **swiveling and adjustable downlight**. Available in mini, small and medium size, with various diameter possibilities, it can be equipped with narrow or wide beam optics. The free rotating body can be partially **extracted and tilted or remain completely recessed**, making **MAKE R** extremely **versatile for office, retail** and all those installations that require **dynamic lighting**.

ID 39

*Where available.

**With accessory: 39AAUGR

MAKE R ^{MINI}


Accessories on page 146.

IP 44

Adjustable and swiveling recessed installation.

Polycarbonate lens Ø 35 mm.

Beam: 24° - 36° - 50°.



Cod. 4000K	☼	lm	Ø mm
390A3K424MN	3W 24°	420	78
390A3K436MN	3W 36°	420	78
390A3K450MN	3W 50°	420	78
390A6K424MN	6W 24°	700	78
390A6K436MN	6W 36°	700	78
390A6K450MN	6W 50°	700	78

Cod. 3000K	☼	lm	Ø mm
390A3K324MN	3W 24°	374	78
390A3K336MN	3W 36°	374	78
390A3K350MN	3W 50°	374	78
390A6K324MN	6W 24°	623	78
390A6K336MN	6W 36°	623	78
390A6K350MN	6W 50°	623	78

MAKE R ^{SMALL}


Accessories on page 146.

IP 44

Adjustable and swiveling recessed installation.

Polycarbonate lens Ø 50 mm.

Beam: 15° - 24° - 36° - 50°.



Cod. 4000K	☼	lm	Ø mm
390A12K415S	12W 15°	1560	138
390A12K424S	12W 24°	1560	138
390A12K436S	12W 36°	1560	138
390A12K450S	12W 50°	1560	138
390A17K415S	17W 15°	2200	138
390A17K424S	17W 24°	2200	138
390A17K436S	17W 36°	2200	138
390A17K450S	17W 50°	2200	138
390A24K415S	24W 15°	3000	138
390A24K424S	24W 24°	3000	138
390A24K436S	24W 36°	3000	138
390A24K450S	24W 50°	3000	138

Cod. 3000K	☼	lm	Ø mm
390A12K315S	12W 15°	1388	138
390A12K324S	12W 24°	1388	138
390A12K336S	12W 36°	1388	138
390A12K350S	12W 50°	1388	138
390A17K315S	17W 15°	1958	138
390A17K324S	17W 24°	1958	138
390A17K336S	17W 36°	1958	138
390A17K350S	17W 50°	1958	138
390A24K315S	24W 15°	2670	138
390A24K324S	24W 24°	2670	138
390A24K336S	24W 36°	2670	138
390A24K350S	24W 50°	2670	138

MAKE R MEDIUM


Accessories on page 146.

IP 44

Adjustable and swiveling recessed installation.

Polycarbonate lens Ø 75 mm.

Beam: 15° - 24° - 36° - 50°.



← Ø 165 →

← Ø 150 →

UGR < 19



Cod. 4000K	☼	lm	Ø mm
390A17K415M	17W 15°	2020	165
390A17K424M	17W 24°	2020	165
390A17K436M	17W 36°	2020	165
390A17K450M	17W 50°	2020	165
390A24K415M	24W 15°	2850	165
390A24K424M	24W 24°	2850	165
390A24K436M	24W 36°	2850	165
390A24K450M	24W 50°	2850	165
390A31K415M	31W 15°	3700	165
390A31K424M	31W 24°	3700	165
390A31K436M	31W 36°	3700	165
390A31K450M	31W 50°	3700	165

Cod. 3000K	☼	lm	Ø mm
390A17K315M	17W 15°	1798	165
390A17K324M	17W 24°	1798	165
390A17K336M	17W 36°	1798	165
390A17K350M	17W 50°	1798	165
390A24K315M	24W 15°	2537	165
390A24K324M	24W 24°	2537	165
390A24K336M	24W 36°	2537	165
390A24K350M	24W 50°	2537	165
390A31K315M	31W 15°	3293	165
390A31K324M	31W 24°	3293	165
390A31K336M	31W 36°	3293	165
390A31K350M	31W 50°	3293	165

DOWNLIGHT

ACCESSORIES



External reflector in chromed PC.

- 39RFRAMN** - MINI
- 39RFRAS** - SMALL
- 39RFRAM** - MEDIUM



External reflector in golden PC.

- 39RFRGMN** - MINI
- 39RFRGS** - SMALL
- 39RFRGM** - MEDIUM



Honeycomb optics - UGR <16.

- 39AANDRMN** - MINI
- 39AANDRS** - SMALL
- 39AANDRM** - MEDIUM



Micro-engraved optics.

- 39AASLRMN** - MINI
- 39AASLRS** - SMALL
- 39AASLRM** - MEDIUM



Frosted glass.

- 39AAVSRMN** - MINI
- 39AAVSRS** - SMALL
- 39AAVSRM** - MEDIUM