

SEMPLICE LED

SEMPLICE LED is an **innovative lighting solution** suited to a wide range of interior applications including commercial, leisure and retail environments. Never before has a product been so versatile, with suspended or directly surface mounted versions available for wall and ceiling mounting. They can be installed individually, continuously mounted or even pattern formed using the tailored range of accessories. Its uniqueness is a **scattered emitted light including the ends**, thanks to the integrated LED technology and translucent end caps. A broad collection of matching products can be implemented for free standing and EU track mounting, giving the user continuity of product and **complete design freedom** in a project.

ID 67



Design
Quargnale // Ruatti studio Architetti

esse-ci

FEATURES



Direct/Indirect emission



UGR < 22



IP 40

LED



3000K/4000K



> 90 lm/W



CRI > 90



Eye safety: RG0/RG1



Mac Adams 3



L80/B10 > 50.000h

CERTIFICATIONS



EEA Conformity



Energy efficiency



5 years warranty



ETL certification

ON REQUEST



DALI - code D*



Emergency 1 hr - code EM
Emergency 3 hrs - code EM3R*



2700K - code K27*
5000K - code K5*



Human Centric Lighting*

SPECIFICATIONS

Integrated driver.
PG optics for soft and homogeneous emission with no shadow areas.
EB optics for side emission.

BODY

Shockproof, antistatic technopolymer with an exclusive paint treatment that guarantees a homogeneous "soft" emission over the entire surface. The ending and junction accessories are made of the same materials, with an invisible coupling fastening system.



* Where available


SEMPlice LED^{PG}


Accessories on page 46.

IP 40

PMMA technopolymer (UGR<22) with surface treatment for completely uniform light distribution. Integrated LED technology.



Cod. 4000K		lm	L mm
67PG24K4HP	24W	2268	624
67PG36K4HP	36W	3402	904
67PG48K4HP	48W	4536	1184
67PG72K4HP	72W	6804	1744
67PG108K4HP	108W	10206	2584



Cod. 3000K		lm	L mm
67PG24K3HP	24W	2155	624
67PG36K3HP	36W	3232	904
67PG48K3HP	48W	4309	1184
67PG72K3HP	72W	6464	1744
67PG108K3HP	108W	9696	2584


SEMPlice LED^{EB}


Accessories on page 46.

IP 40

PMMA technopolymer (UGR<22) with surface treatment and super-pure aluminum reflector for bi-directional light distribution. Integrated LED technology.




Cod. 4000K		lm	L mm
67EB24K4HP	24W	2167	624
67EB36K4HP	36W	3251	904
67EB48K4HP	48W	4334	1184
67EB72K4HP	72W	6502	1744
67EB108K4HP	108W	9752	2584


Cod. 3000K		lm	L mm
67EB24K3HP	24W	2059	624
67EB36K3HP	36W	3088	904
67EB48K3HP	48W	4118	1184
67EB72K3HP	72W	6176	1744
67EB108K3HP	108W	9265	2584


SEMPLICE LED EUTRACK

IP 40

PMMA technopolymer (UGR<22) with surface treatment for completely uniform light distribution. Integrated LED technology. Fitted with EU Track connector.



Cod. 4000K		lm	L mm
67PG24K4HPAB	24W	2268	624
67PG36K4HPAB	36W	3402	904
67PG48K4HPAB	48W	4536	1184
67PG72K4HPAB	72W	6804	1744
67PG108K4HPAB	108W	10206	2584

Cod. 3000K		lm	L mm
67PG24K3HPAB	24W	2155	624
67PG36K3HPAB	36W	3232	904
67PG48K3HPAB	48W	4309	1184
67PG72K3HPAB	72W	6464	1744
67PG108K3HPAB	108W	9696	2584

ACCESSORIES



Single adjustable suspension kit.
Length: 1500 / 3000mm.

67AA13
67AA1330



Spacers kit for wall/ceiling mount.

67AA14



3 - 5 poles ceiling power supply box.
Cable length 2000mm

00AA16
00AA165P



Electrified linear joint with total emission for continuous rows installation.

67AA1LED



Internally electrified creative joint for horizontal change of direction.

67AA05



Internally electrified 90° joint for vertical change of direction.

67AA05V