STYLO LV

ID 88





STYLO LV ZOOM



STYLO LV

CE | E | RETILAP

5 YEARS WARRANTY

IP 40 | CRI>90 | MacAdam 3

IK 02 | RG0/RG1 | L90/B10 50.000h

-20° +35°


48 V

Body

Die-cast aluminum with epoxy powder coating

STYLO LV / ZOOM

Lens with adjustable beam from 10°-40°.






Power box included and 1500mm cable.

CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
88ZM3K4LV	262	88ZM3K3LV	238	3W	31
88ZM5K4LV	560	88ZM5K3LV	510	5W	31

For the version compatible with TWOS 48V track module, add "MC" to the code.

STYLO LV

Policarbonate lens, 25°-40° beam angle.





Power box included and 1500mm cable.

CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
88PC5K425LV	360	88PC5K325LV	318	5W 25°	36
88PC5K440LV	360	88PC5K340LV	318	5W 40°	36
88PC8K425LV	574	88PC8K325LV	508	8W 25°	36
88PC8K440LV	574	88PC8K340LV	508	8W 40°	36

For the version compatible with TWOS 48V track module, add "MC" to the code.

ACCESSORIES



Honeycomb optics for Stylo LV.

88AAND



Decorative frontal ring for Stylo LV.

88AASD



External ring.

88RFA - Chromed
88RFG - Gold
88RFW - White
88RFBK - Black

CE | E | RETILAP

5 YEARS WARRANTY

IP 40 | CRI>90 | MacAdam 3

IK 02 | RG0/RG1 | L90/B10 50.000h

-20° +35°

48 V

On req.: DALI CODE — D | BT

CODE K27 2700K | CODE K5 5000K

CODE DIMTDS SWITCHDIM

Body

Die-cast aluminum with epoxy powder coating

Colours

COD.W | COD.BK | + ON REQ.

