

FEATURES

-  Direct emission
-  UGR <19
-  IP 40

LED

-  3000K/4000K
-  >72 lm/W
-  CRI >90
-  Eye safety: RG0/RG1
-  Mac Adams 3
-  L80/B10 >50.000h

CERTIFICATIONS

-  EEA Conformity
-  Energy efficiency
-  5 years warranty

ON REQUEST

-  DALI - code D*
-  Bluetooth - code BT*
-  2700K - code K27*
5000K - code K5*

SPECIFICATIONS

25°- 40° polycarbonate lens.
Honeycomb optic.
Diffusing decorative screen.

BODY

Die-cast aluminum with
epoxy powder coating.

COLORS

White RAL 9003 wrinkled
- code W
Black RAL 9005 wrinkled
- code BK

RELATED PRODUCTS

Stylo Suspended (P. 98)
LV Track (P. 184)

*Where available
For SWITCHDIM command use DIMTDS (pg. 337)



STYLO LV

STYLO LV is a **miniaturized suspended element** with a minimal but elegant design that can be installed on low voltage 48V tracks. Excellent glare control through a cut-off angle of over thirty degrees.

ID 88



LOW VOLTAGE

esse-ci


STYLO LV

IP 40

Polycarbonate lens. Beam angles: 25°-40°.

1.5 m of suspension / power supply cable included..

Power supply box requested for installation, see accesories.



Cod. 4000K		lm	Ø mm
88PC5K425	5W 25°	360	36
88PC5K440	5W 40°	360	36
88PC8K425	8W 25°	574	36
88PC8K440	8W 40°	574	36

Cod. 3000K		lm	Ø mm
88PC5K325	5W 25°	318	36
88PC5K340	5W 40°	318	36
88PC8K325	8W 25°	508	36
88PC8K340	8W 40°	508	36

ACCESSORIES



Power supply box for
Low Voltage 48V track,
ON/OFF version.

88AA16ABLVD



Power supply box for
Low Voltage 48V track,
DALI version.

88AA16ABLVD



Honeycomb optics

88AAND



Diffusing PG
decorative screen.

88AASD