






STYLO

STYLO is a **miniaturized suspended element** with an elegant design that can be installed **individually** or three-phase tracks. Excellent glare control through a cut-off angle of over thirty degrees.







ID 88



FEATURES

-  Direct emission
-  UGR <19
-  IP 40

LED

-  3000K/4000K
-  >72 lm/W
-  CRI >90
-  Eye safety: R60/R61
-  Mac Adams 3
-  L80/B10 >50.000h

CERTIFICATIONS

-  EEA Conformity
-  Energy efficiency
-  5 years warranty

ON REQUEST

-  DALI - code D
-  2700K - code K27*
5000K - code K5*

SPECIFICATIONS

25° - 40° polycarbonate lens.
Honeycomb optic.
Diffusing decorative screen.

BODY

Aluminum with epoxy powder coating.

COLORS

White RAL 9003 wrinkled
- code W
Black RAL 9005 wrinkled
- code BK


RELATED PRODUCTS

Stylo LV (P. 225)

STYLO

IP 40

Polycarbonate lens, 25° - 40° beam angle.
Complete with 1.5mt cable. Needs powered supply box.



Cod. 4000K	Icon	lm	Ø mm
88PC5K425	5W 25°	360	36
88PC5K440	5W 40°	360	36
88PC8K425	8W 25°	574	36
88PC8K440	8W 40°	574	36

Cod. 3000K	Icon	lm	Ø mm
88PC5K325	5W 25°	318	36
88PC5K340	5W 40°	318	36
88PC8K325	8W 25°	508	36
88PC8K340	8W 40°	508	36

ACCESSORIES



Power supply box with built-in driver, for ceiling installation.

88AA16



Power supply box with built-in driver, for ceiling installation, DALI version.

88AA16D



Power supply box with built-in driver, for recessed installation.

88AA16R



Power supply box with built-in driver, for recessed installation, DALI version.

88AA16RD



Honeycomb optics.

88AAND



Diffusing decorative PG screen.

88AASD