TRILLY

ID 01





TRILLY



TRILLY DIRECT



TRILLY FABRIC

CE | E | RETILAP | 5 YEARS WARRANTY | III

IP 40 | -20° +35° | CRI>90 | RG0/RG1 | MacAdam 3 | L90/B10 50.000h | 48 V

Body

Die-cast aluminium

TRILLY

Element for single installation with semi-transparent silicone diffuser.





CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
01DSL3K4	334	01DSL3K3	310	3W	100

CCT. 2700K	lm	Led	Ømm
01DSL3K27	292	3W	100

TRILLY / DIRECT

Element for single installation with aluminum diffuser.





CCT. 4000K	lm	CCT. 3000K	lm	Led	Ømm
01DA3K4	293	01DA3K3	272	3W	100

CCT. 2700K	lm	Led	Ømm
01DA3K27	256	3W	100

CE | E | RETILAP | 5 YEARS WARRANTY | III

IP 40 | -20° +35° | CRI>90 | RG0/RG1 | MacAdam 3 | L90/B10 50.000h | 48 V

On req.: DALI CODE — D | BT

Body

Die-cast aluminium

Colours

COD.W | COD.BK

TRILLY / FABRIC

Element for single installation with decorative reflector in thermally bonded grey wadding with black edge.





CCT. 4000K	lm
01DD3K4	364

CCT. 3000K	lm
01DD3K3	340

Led	Ømm
3W	100

CCT. 2700K	lm
01DD3K27	319

Led	Ømm
3W	100

ACCESSORIES



Ceiling powered supply box with 2000mm cable.

01AA16

DALI version.

01AA16D



Recessed ceiling mount with driver for suspension installation, with 2000mm cable.

01AA16R

DALI version.

01AA16RD



Rectangular box kit with driver for 3x, 5x or 7x multiple suspension installation, with 2000mm cable.

01BX163X
01BX165X
01BX167X

DALI version.

01BX163XD
01BX165XD
01BX167XD



Circular box kit with driver for 3x, 5x or 7x multiple suspension installation, with 2000 mm cable.

01BR163X
01BR165X
01BR167X

DALI version.

01BR163XD
01BR165XD
01BR167XD



Power supply/suspension for Low Voltage 48V track with 2000 mm cable.

01AA16LV

DALI version.

01AA16LVD



Connection for Ghostfeed 2.0 with 2000 mm cable.

01AA16GF